

Accuchiller

TCFW350 Series



Delivers exceptional part load efficiency



Intuitive PLC control with a user-friendly text display



Hybrid film evaporator for the most efficient heat transfer

CENTRAL CHILLER

Single Circuit
100 tons (352 kW)

Thermal Care is at the forefront of process cooling technology. TC Series industrial central chillers feature revolutionary, frictionless, magnetic bearing Turbocor compressors for optimal performance and unmatched part load efficiency. The oil-free design eliminates oil management systems, reducing costs and environmental impact while enhancing reliability.

TCF Central Chillers combine the energy saving benefits of a wet (flooded) system with the efficiency and flexibility of a variable-speed centrifugal compressor. This unique design delivers exceptional performance, reduced refrigerant usage, and a smaller physical footprint.

TCF Series chillers feature an intuitive PLC system with a 7" HMI high resolution LCD color touch screen for precise control and monitoring. The user-friendly interface provides real-time system data, allowing users to monitor system operating conditions, adjust parameters, and troubleshoot with ease. Clear text displays, graphics, and time stamped fault logs, simplify operation and maintenance. The PLC system can manage up to six refrigeration circuits, optimizing performance and diagnostics.

Discover how the TC Series can revolutionize your process cooling operations.



Lower Global Warming Potential	Featuring Opteon™ XP10 (R-513A) Refrigerant with low toxicity and low flammability.
Variable-Speed Compressor	Direct-drive variable-speed centrifugal compressor technology continuously adjusts speed to match load to reduce operating costs.
Magnetic Bearing	A magnetic field levitates the drive shaft and eliminates the friction of conventional bearings for higher efficiencies and an oil-free refrigeration system.
Integral Variable Speed Drive	High-efficiency brushless DC motor with built-in variable-speed drive technology is refrigerant cooled, compact, and energy efficient.
Soft Start	The variable-speed drive limits soft-starts to 2 amps inrush current per compressor to reduce peak energy demand and extend compressor motor life.
Low Noise Operation	The magnetic bearings keep the drive shaft in position under high-speed operation for virtually no structural vibration and low noise.
Compressor Rotary Circuit Breaker	A through-the-door rotary circuit breaker for each compressor allows easy maintenance of a compressor without the need to shut down power to the chiller.
UL 508A Industrial Control Panel	Every chiller has a UL label certifying the panel design and components comply with UL 508A standards ensuring the panels are safe and consistent for reliable operation.
Hybrid Film Evaporator	Advanced design provides the most efficient heat transfer while minimizing the refrigerant charge requirement results in a compact, extremely energy-efficient unit.
Advanced Controls with Color Touch Screen	7-inch color touch screen shows chiller operation for quick and easy monitoring and control of the system. Can control up to six chillers.
CONNEX4.0 Ready Controls	Equipped with an Ethernet port and is fully compatible with the CONNEX4.0 plant wide equipment control and monitoring system.
Modular Expandable System	Allows for flexible system design and provides for system expansion to over 600 tons (2,110 kW) using up to six chillers.
Warranty	1 year parts and labor.

